

DATA SHEET

Retractable Universal Mount 4K HDMI[®] Dongle Adapter Ring with Color Coded Mini DisplayPort[™], DisplayPort, and USB-C[®]

Attach a Retractable Universal Cable Mount with color-coded dongle adapters to an HDMI cable to provide connectivity options for a meeting space display

OVERVIEW

The Patent Pending Retractable Universal 4K HDMI Dongle Adapter Ring is the perfect addition to conference rooms, huddle spaces, lecture halls, or classrooms to make sure that anyone can connect. The standard configuration includes the adapters to connect nearly any device to the in-room display while supporting up to a 4K video resolution. Choose from HDMI to DisplayPort, Mini DisplayPort, or USB-C to meet connectivity challenges.

Dongle Style Adapter

It can be awkward when connecting an adapter to a smaller laptop or tablet. The adapter may not line up correctly, causing the computer to shift or not set flat on the table. The dongle style adapter gives more flexibility, allowing for better placement when connecting to thin or lighter weight laptops.

Color Coded Adapters

Each adapter is color-coded with a band that saves time and frustration by making it easy to identify the adapter you need quickly.

Integrated Pull Tab

Quickly grab the adapters when you need them with the integrated Pull Tab that is also available to be customized to feature your company or organization logo. Minimum order quantities apply to customized Pull Tabs.

Retractable Universal Cable Mount

The Retractable Universal Mount attaches to any flat surface, like a table or lectern, providing mounting flexibility to fit your environment best. The retractor extends out to 4.9ft, ensuring that the adapters are always within reach when needed, and the retractor tested to over 20,000 extension cycles for long service life.

Tools Included

To simplify the process, the installation tool is included.

FEATURES

- Adapters support up to a 4K video resolution, so meeting attendees will be able to see the displayed content for improved comprehension and detailed decision making
- Dongle style adapter, allowing for more flexibility when connecting to a laptop or tablet
- Adapters are color coded, so no more frustration trying to find the adapter that you typically use for your laptop
- Integrated pull tab, so the adapters can be accessed quickly or easily reached when they are tucked away
- Installation tools are included, so you save time and money by not needing to purchase any additional tools

ITEM	DESCRIPTION
------	-------------

C2G30029	Retractable Universal Mount 4K HDMI Dongle Adapter Ring with Color Coded Mini DisplayPort , DisplayPort, and USB-C
----------	--

SIGNAL SPECIFICATIONS

- USB Type-C to HDMI Dongle: 100% Functional Test at 4K/60Hz/4:4:4 Resolution with Standard AV Test Equipment
- DisplayPort to HDMI Dongle: 100% Functional Test at 4K/30Hz Resolution with Standard AV Test Equipment
- Mini DisplayPort to HDMI Dongle: 100% Functional Test at 4K/30Hz Resolution with Standard AV Test Equipment

ELECTRICAL SPECIFICATIONS

- Rating: Temp 80°C; Voltage 30V
- Conductor Resistance: At 20°C Max 32AWG: mDP/DP: 588.85 OHMS/KM; USB-C: 588 OHMS/KM; 24AWG: 86 OHMS/KM
- Insulation Resistance: mDP/DP: 10M OHMS/KM Min at 20°C DC 500V
- Insulation Resistance: USB-C: PP/HD-PE DC 500V 100M OHMS/KM Min at 20°C
- Dielectric Strength: AC 500V/1 Minute No Breakdown

PHYSICAL SPECIFICATIONS


- Operating Temperature: 0°C - 40°C (0% - 90%RH)
- Storage Temperature: -10°C - 60°C (0% - 90%RH)
- mDP/DP Minimum Bend Radius: R52mm
- USB-C Minimum Bend Radius: R45mm
- Cables Jacket Rating: VW-1
- Tensile Strength: Unaged: 1500PSI Min, Aged: 70% Min

PHYSICAL CHARACTERISTICS


- HDMI Female: Solder Type, Contacts: Brass, Gold Flash, Housing: LCP, Black with PCB, Shell: SPCC, Gold Plated
- USB Type-C Male: Solder Type, Contacts: Brass, Gold Flash, Housing: LCP, Black, Shell: Gold Plated
- DisplayPort Male: Solder Type, Contacts: Gold Flash, Housing: LCP Black, Shell: Gold Plated (with Latches)
- Mini DisplayPort Male: Solder Type, Contacts: Gold Flash, Housing: LCP Black, Shell: Gold Plated
- All Hoods: Molded Black PVC
- USB Type-C to HDMI Adapter Color Band: Green
- DisplayPort to HDMI Adapter Color Band: Red
- Mini DisplayPort to HDMI Adapter Color Band: Yellow
- Retractor: 63.5x63.5x17.5mm, Black Steel Wire OD: 1.2mm, Retracting Cable Length: 6ft, ABS Shell, with Hex Nut Tool and Black Locking Coupler (x2)
- Black Metal Screws (x4): 6.8x22mm, M3, Material: Steel
- Black Metal Screws (x4): 6.0x22.5mm, M3.5, Material: Steel
- PC Eyelet: 17.8x4.7x2.6mm, Black, Material: PC
- Pull Tab: 80x25x2mm, Material: Polyester, Black Background, White Text, with Black Eyelet
- Universal Mounting Bracket: 85x65x1.2mm, Material: C.R.S. Rigidity: 1/4H, Color: Black
- Product is CE marked and conforms to 2011/65/EU ROHS 2

Retractable Universal Mount 4K HDMI Dongle Adapter Ring Side View


- Mini DisplayPort
- DisplayPort
- USB-C




Mini DisplayPort Detail




DisplayPort Detail



USB-C Detail



Retractable Mount Detail



LEGRAND | AV COMMERCIAL BRANDS

C2G | Chief | Da-Lite | Luxul | Middle Atlantic | Vaddio | Wiremold

SIMPLIFIED CONNECTIVITY

USA 800.506.9607 | c2g.com | legrandav.com | customer-service@c2g.com

EMEA +31 495 580 840 | c2g.com/uk | legrandav.com | c2g.emea@av.legrand.com

©2021 Legrand AV Inc. 210490 Rev A 7/20 C2G is a registered trademark of Legrand AV Inc. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All patents are protected under existing designations. Other patents pending.